


KANA SUSKB ステンレスかさ歯車 NEW


●ご注文方法 商品コード

SUSKB2-30 20

モジュール 歯数 相手方歯数



M3形状



M4形状

i	精度等級	JIS B 1704 3級
	歯形	グリーンゾン
	圧力角	20°
m	材質	ステンレス SUS303
	熱処理	-
h	歯面硬度	HB187以下
s	表面処理	-

商品コード	定価 (円)	歯数比	モジュール (m)	歯数	穴径 d _{H7}	ボス径 BD	歯先円直径 Do	基準円直径 Dp	組立距離 C	全長 BL	歯先距離 G	ボス長さ H	穴長さ l	歯幅 T	おさえ面径 K	形状	質量 (kg)	商品コード
SUSKB1.5-3020	4,200	1.5	1.5	30	10	30	46.24	45	28	18.53	13.93	8	16	9	27.37	M4	0.12	SUSKB1.5-3020
SUSKB1.5-2030	2,600			20	8	25	33.13	30	33	18.63	11.54	8.83	17	9	17.05	M3	0.06	SUSKB1.5-2030
SUSKB2 -3020	6,600	1.5	2	30	10	35	61.65	60	40	26.87	21.24	15	23	11	37.56	M4	0.27	SUSKB2 -3020
SUSKB2 -2030	4,100			20	10	35	44.18	40	45	25.06	16.39	13.33	22	11	21.34	M3	0.16	SUSKB2 -2030
SUSKB2.5-3020	10,200	1.5	2.5	30	15	45	77.07	75	50	34.22	26.55	18	30	15	45.61	M4	0.55	SUSKB2.5-3020
SUSKB2.5-2030	5,600			20	12	40	55.22	50	55	31.06	19.24	14.16	28	15	27.42	M3	0.29	SUSKB2.5-2030
SUSKB3 -3020	14,400	1.5	3	30	15	60	92.48	90	55	35.56	26.86	17	31	17	57.14	M4	0.95	SUSKB3 -3020
SUSKB3 -2030	9,000			20	15	50	66.27	60	70	40.48	27.09	21.66	37	17	34.71	M3	0.56	SUSKB3 -2030
SUSKB1.5-4020	6,700	2	1.5	40	10	38	60.88	60	35	25.01	20.88	15	22	10	39.64	M4	0.27	SUSKB1.5-4020
SUSKB1.5-2040	3,000			20	8	25	33.61	30	46	25.54	16.9	14.75	24	10	17.28	M3	0.09	SUSKB1.5-2040
SUSKB2 -4020	11,000	2	2	40	12	50	81.17	80	45	32.37	26.17	18	27	15	48.46	M4	0.62	SUSKB2 -4020
SUSKB2 -2040	4,600			20	12	32	44.81	40	60	34.16	21.2	18	32	15	20.92	M3	0.19	SUSKB2 -2040
SUSKB2.5-4020	18,900	2	2.5	40	15	60	101.46	100	55	39.73	31.46	20	35	20	60.28	M4	1.2	SUSKB2.5-4020
SUSKB2.5-2040	7,500			20	12	40	56.01	50	75	43.78	26.5	22.5	41	20	24.56	M3	0.41	SUSKB2.5-2040
SUSKB3 -4020	27,400	2	3	40	20	70	121.76	120	65	45.85	36.76	24	38	22	73.81	M4	1.9	SUSKB3 -4020
SUSKB3 -2040	10,600			20	16	50	67.22	60	90	50.81	31.8	27.5	47	22	29.61	M3	0.7	SUSKB3 -2040
SUSKB1.5-4515	7,200	3	1.5	45	10	36	68.06	67.5	28	20.44	17.59	11	17	10	46.58	M4	0.25	SUSKB1.5-4515
SUSKB1.5-1545	2,100			15	8	18	26.54	22.5	47	23.19	13.92	12.5	22.5	10	14.75	M3	0.04	SUSKB1.5-1545
SUSKB2 -4515	12,800	3	2	45	12	60	90.75	90	40	30.4	26.12	17	26	15	59.04	M4	0.82	SUSKB2 -4515
SUSKB2 -1545	3,100			15	10	24	35.35	30	60	29.8	15.89	14	29	15	19.13	M3	0.1	SUSKB2 -1545
SUSKB2.5-4515	21,700	3	2.5	45	15	60	113.43	112.5	50	38.35	32.65	22	35	20	72.84	M4	1.4	SUSKB2.5-4515
SUSKB2.5-1545	4,500			15	12	30	44.18	37.5	75	38.41	19.86	17.5	37	20	20.51	M3	0.19	SUSKB2.5-1545
SUSKB3 -4515	30,900	3	3	45	20	80	136.12	135	55	40.74	34.18	20	35	24	88.18	M4	2.4	SUSKB3 -4515
SUSKB3 -1545	6,700			15	15	38	53.02	45	90	45.17	23.84	21.33	43	23	22.53	M3	0.34	SUSKB3 -1545

※KANAギヤセットでのご使用を推奨いたします。