

# KANA KSM 焼入スパイラルマイタギヤ NEW



## ●ご注文方法 商品コード

**KSM2-20R**

モジュール 歯数 L


ねじれ方向

ねじれ方向  
R=右  
L=左



R(右)

L(左)



M3形状

i	精度等級	JIS B 1704 4級
	歯形	グリーソン
	圧力角	20°
	ねじれ角	35°
m	材質	機械構造用炭素鋼
h	熱処理	歯面高周波焼入
s	歯面硬度	HRC50~60
	表面処理	黒染

商品コード	定価 (円)	モジュール (m)	歯数	穴径 d <sub>H7</sub>	ボス径 BD	歯先円直径 Do	基準円直径 Dp	組立距離 C	全長 BL	歯先距離 G	ボス長さ H	穴長さ I	歯幅 T	おさえ面径 K	形状	質量 (kg)	商品コード
KSM1 -20R	1,400	1	20	6	16	21.3	20	20	13.84	10.65	8	12	5	9.86	M3	0.02	KSM1 -20R
KSM1 -20L	1,400																KSM1 -20L
KSM1.5-20R	1,700	1.5	20	8	26	31.74	30	30	21.18	15.87	13	19	8	15.37		0.07	KSM1.5-20R
KSM1.5-20L	1,700																KSM1.5-20L
KSM2 -20R	2,100	2	20	12	34	42.4	40	37	24.75	18.2	14	22	10	21.72		0.15	KSM2 -20R
KSM2 -20L	2,100																KSM2 -20L
KSM2.5-20R	3,600	2.5	20	14	42	52.94	50	48	32.42	24.47	19	29	12	28.06		0.30	KSM2.5-20R
KSM2.5-20L	3,600																KSM2.5-20L
KSM3 -20R	4,500	3	20	16	50	63.72	60	58	39.6	29.86	23	35	15	31.57		0.52	KSM3 -20R
KSM3 -20L	4,500																KSM3 -20L
KSM3.5-20R	6,100	3.5	20	20	60	74.47	70	65	43.81	32.23	25	40	18	39.09	0.82	KSM3.5-20R	
KSM3.5-20L	6,100															KSM3.5-20L	
KSM4 -20R	7,400	4	20	20	64	84.88	80	75	50.51	37.44	27	45	20	43.43	1.2	KSM4 -20R	
KSM4 -20L	7,400															KSM4 -20L	
KSM5 -20R	11,900	5	20	25	80	105.9	100	90	60.16	42.95	30	54	26	54.46	2.1	KSM5 -20R	
KSM5 -20L	11,900															KSM5 -20L	
KSM6 -20R	20,900	6	20	28	100	127.16	120	104	67.35	47.58	34	60	30	67.15	3.7	KSM6 -20R	
KSM6 -20L	20,900															KSM6 -20L	
KSM8 -20R	32,100	8	20	30	130	169.94	160	125	72.6	49.97	30	62	35	95	7.0	KSM8 -20R	
KSM8 -20L	32,100															KSM8 -20L	

※KANAギヤセットでのご使用を推奨いたします。

# KANA KSM 焼入スパイラルマイタギヤ



## ●ご注文方法 商品コード

**KSM2-20R**

モジュール 歯数 L


ねじれ方向

ねじれ方向  
R=右  
L=左



R(右)

L(左)



M3形状

i	精度等級	JIS B 1704 4級
	歯形	グリーソン
m	圧力角	20°
	ねじれ角	35°
h	材質	機械構造用炭素鋼
	熱処理	歯面高周波焼入
s	歯面硬度	HRC50~60
	表面処理	黒染

商品コード	定価(円)	モジュール(m)	歯数	穴径 d <sub>H7</sub>	ボス径 BD	歯先円直径 Do	基準円直径 Dp	組立距離 C	全長 BL	歯先距離 G	ボス長さ H	穴長さ I	歯幅 T	おさえ面径 K	形状	質量(kg)	商品コード					
KSM1 -25R	1,600	1	25	6	20	26.22	25	23	15.08	11.11	8	14	6	15.03	M3	0.04	KSM1 -25R					
KSM1 -25L	1,600																KSM1 -25L					
KSM1.5-25R	2,100	1.5	25	10	30	39.31	37.5	34	22.14	16.16	11.5	19	19.54	M3		0.11	KSM1.5-25R					
KSM1.5-25L	2,100																KSM1.5-25L					
KSM2 -25R	2,600	2	25	12	40	52.38	50	40	24.2	16.19	10	20	12			26.06	M3	0.21	KSM2 -25R			
KSM2 -25L	2,600																		KSM2 -25L			
KSM2.5-25R	4,400	2.5	25	16	50	65.54	62.5	50	30.24	20.27	12.5	26	15			34.57		M3	0.42	KSM2.5-25R		
KSM2.5-25L	4,400																			KSM2.5-25L		
KSM3 -25R	5,700	3	25	20	60	78.77	75	60	37.57	24.39	15	32	20			37.43			M3	0.74	KSM3 -25R	
KSM3 -25L	5,700																				KSM3 -25L	
KSM3.5-25R	7,500	3.5	25	25	70	91.81	87.5	70	42.98	28.41	17.5	37	22			46.77				M3	1.1	KSM3.5-25R
KSM3.5-25L	7,500																					KSM3.5-25L
KSM4 -25R	9,800	4	25	28	80	104.7	100	80	49.14	32.35	20	43	25		55.29	M3					1.7	KSM4 -25R
KSM4 -25L	9,800																					KSM4 -25L
KSM5 -25R	16,900	5	25	28	100	130.86	125	100	60.59	40.43	25	50	30	65.15	M3						3.4	KSM5 -25R
KSM5 -25L	16,900																					KSM5 -25L
KSM6 -25R	26,500	6	25	28	120	157.17	150	120	71.97	48.58	30	61	35	83			M3				6.0	KSM6 -25R
KSM6 -25L	26,500																					KSM6 -25L
KSM1 -30R	2,000	1	30	8	24	31.26	30	28	17.61	13.63	10	16	6	19.03				M3			0.06	KSM1 -30R
KSM1 -30L	2,000																					KSM1 -30L
KSM1.5-30R	2,600	1.5	30	10	36	46.84	45	43	28.11	21.42	16	25	10	25.72					M3		0.21	KSM1.5-30R
KSM1.5-30L	2,600																					KSM1.5-30L
KSM2 -30R	4,000	2	30	12	45	62.42	60	50	29.27	21.21	12.5	25	12	36.06						M3	0.37	KSM2 -30R
KSM2 -30L	4,000																					KSM2 -30L
KSM2.5-30R	5,600	2.5	30	16	60	78.04	75	62	36.08	26.02	17	32	15	47.57		M3					0.76	KSM2.5-30R
KSM2.5-30L	5,600																					KSM2.5-30L
KSM3 -30R	7,700	3	30	20	70	93.61	90	75	45.25	31.8	20	40	20	53.43	M3						1.3	KSM3 -30R
KSM3 -30L	7,700																					KSM3 -30L
KSM3.5-30R	10,400	3.5	30	25	90	109.21	105	85	49.4	34.6	25	45	22	67.77			M3				2.2	KSM3.5-30R
KSM3.5-30L	10,400																					KSM3.5-30L
KSM4 -30R	13,500	4	30	28	100	124.71	120	95	54.28	37.35	25	50	25	79.29				M3			3.1	KSM4 -30R
KSM4 -30L	13,500																					KSM4 -30L
KSM5 -30R	27,200	5	30	28	130	155.90	150	120	68.2	47.95	35	62	30	99.15					M3		6.4	KSM5 -30R
KSM5 -30L	27,200																					KSM5 -30L

※KANAギヤセットでのご使用を推奨いたします。