


# 2080B

## Standard Double Pitch Sprocket for S Rollers B-type

### Order Product Code


**2080B 6 1/2**

TYPE	No. of Active Teeth
Sprocket No.	



- Chain ..... **No.C2080H**
- Chain Pitch ..... **( P ) 50.80 mm**
- Roller Link Inner Width ..... **( W ) 15.88 mm**
- Roller Outside Diameter ..... **( Dr ) 15.88 mm**
- Tooth Width ..... **( T ) 14.6 mm**

TYPE	No. of Active Teeth	Actual No. of Teeth	Do	Dp	Shaft Hole Diameter d			BD	BL	Shape	Tooth Section	Weight kg
					Prepared Hole	Minimum	Maximum					
<b>2080B</b>	6 1/2	13	118	109.312	16	17	46	70	40	Ground Specification	 High-frequency Hardened Teeth	1.62
	7 1/2	15	135	124.897	20	21	60	88	40			2.34
	8 1/2	17	151	140.626	20	21	63	93	40			2.48
	9 1/2	19	167	156.452	20	21	63	93	40			3.24
	10 1/2	21	184	172.346	20	21	63	93	40	Ground Specification	 Carbon Structural Steel	3.68
	11 1/2	23	200	188.290	26	27	75	107	45			4.88
	12	24	208	196.276	26	27	75	107	45			5.30
	12 1/2	25	216	204.270	26	27	75	107	45			5.43



Use together with the KANA machine key.  
Refer to P.334 to P.335