



2082B

Standard Double Pitch Sprocket for R Rollers B-type

Order Product Code




Ground Specification **Welded Specification**



Ground Specification **Welded Specification**

- Chain **No. C2082H**
- Chain Pitch **(P) 50.80 mm**
- Roller Link Inner Width **(W) 15.88 mm**
- Roller Outside Diameter **(Dr) 28.58 mm**
- Tooth Width **(T) 14.6 mm**

TYPE	No. of Active Teeth	Do	Dp	Shaft Hole Diameter d			BD	BL	Shape	Tooth Section	Weight kg
				Prepared Hole	Minimum	Maximum					
2082B	7	136	117.082	22	23	50	76	40	Ground Specification	Carbon Structural Steel	1.85
	8	153	132.747	22	23	60	93	40			2.64
	9	170	148.529	26	27	65	110	40			3.56
	10	187	164.392	26	27	63	93	40			3.29
	11	204	180.313	26	27	75	107	45			4.42
	12	220	196.276	26	27	75	107	45			4.94
	13	237	212.272	26	27	75	107	45			5.46
	14	253	228.293	26	27	75	107	45			6.09
	15	269	244.335	30	31	75	107	45			6.70
	16	286	260.392	30	31	75	107	45			7.42
	17	302	276.463	30	31	75	107	45			8.12
	18	319	292.546	30	31	80	117	50	9.76		
	19	335	308.637	30	31	80	117	50	10.56		
	20	351	324.737	30	31	80	117	50	Welded Specification	Common Steel	11.46
	24	416	389.194	35	36	80	117	50			16.30
	25	433	405.319	35	36	80	117	50			17.50
	26	449	421.448	35	36	80	117	50			18.70
	28	481	453.715	35	36	80	117	50			21.20
	30	514	485.992	35	36	80	117	50			24.00



Use together with the KANA machine key.
Refer to P.334 to P.335