



# 2100B

## Standard Double Pitch Sprocket for S Rollers B-type

### Order Product Code

**2100B 6 1/2**



- Chain ..... **No.C2100H**
- Chain Pitch ..... **( P ) 63.50 mm**
- Roller Link Inner Width ..... **( W ) 19.05 mm**
- Roller Outside Diameter ..... **( Dr ) 19.05 mm**
- Tooth Width ..... **( T ) 17.6 mm**

TYPE	No. of Active Teeth	Actual No. of Teeth	Do	Dp	Shaft Hole Diameter d			BD	BL	Shape	Tooth Section	Weight kg
					Prepared Hole	Minimum	Maximum					
<b>2100B</b>	6 1/2	13	148	136.640	20	21	60	88	50	Ground Specification	High-frequency Hardened Teeth	3.38
	7 1/2	15	168	156.121	20	21	66	98	50			4.12
	8 1/2	17	189	175.783	20	21	75	107	50			5.15
	9 1/2	19	209	195.565	20	21	75	107	50			5.91
	10 1/2	21	230	215.433	20	21	75	107	50			6.76
	11 1/2	23	250	235.362	26	27	80	117	56	Ground Specification		8.63
	12 1/2	25	270	255.338	26	27	80	117	56			9.65



Use together with the KANA machine key.  
Refer to P.334 to P.335