


25A

Standard Sprocket A-type

● Order Product Code

25A 16
 TYPE No. of Teeth
 Sprocket No.



- Chain **No.25**
- Chain Pitch **(P) 6.35 mm**
- Bushing Link Inner Width **(W) 3.18 mm**
- Bushing Outside Diameter **(Dr) 3.30 mm**
- Tooth Width **(T) 2.8 mm**

m Common Steel

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		Weight kg
				Prepared Hole	Minimum	
25A	10	23	20.549	6	7	0.01
	12	28	24.535	7	8	0.01
	13	30	26.534	7	8	0.01
	14	32	28.537	7	8	0.01
	15	34	30.542	7	8	0.02
	16	36	32.549	9	10	0.02
	17	38	34.558	9	10	0.02
	18	40	36.568	9	10	0.02
	20	44	40.592	9	10	0.03
	24	52	48.649	9	10	0.04
	25	54	50.665	9	10	0.04
	27	58	54.698	9	10	0.05
	28	60	56.714	9	10	0.06
	29	62	58.732	9	10	0.06
	30	64	60.749	9	10	0.06
	32	68	64.785	10	11	0.07
	33	70	66.803	10	11	0.08
	35	74	70.839	10	11	0.09
	36	76	72.858	10	11	0.09
	37	78	74.877	10	11	0.10
	38	80	76.896	10	11	0.10
	40	84	80.934	10	11	0.11
	42	89	84.972	11	12	0.12
	45	95	91.031	11	12	0.14
50	105	101.130	11	12	0.18	
55	115	111.230	11	12	0.21	
60	125	121.331	11	12	0.25	
70	145	141.536	11	12	0.34	
75	155	151.639	11	12	0.40	
80	165	161.743	11	12	0.45	