



35SD

SD Single-Double Sprocket

Order Product Code

35SD 20

TYPE No. of Teeth
Sprocket No.



Use together with the KANA machine key. Refer to P.334 to P.335

- ChainNo.35
- Chain Pitch(P) 9.525 mm
- Bushing Link Inner Width(W) 4.78 mm
- Bushing Outside Diameter(Dr) 5.08 mm
- Tooth Width(T) 4.3 mm (C) 15.7mm

- m Carbon Structural Steel
- h High-frequency Hardened Teeth

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d			BD	BL	Weight kg
				Prepared Hole	Minimum	Maximum			
35SD	12	41	36.802	10	11	15	24	20	0.12
	13	44	39.801	10	11	16	28	20	0.13
	14	47	42.805	10	11	16	30	20	0.15
	15	51	45.813	10	11	20	35	20	0.19
	16	54	48.824	10	11	20	37	20	0.22
	17	57	51.837	10	11	25	41	20	0.25
	18	60	54.852	10	11	25	44	20	0.28
	19	63	57.869	10	11	28	47	20	0.32
	20	66	60.888	12	13	30	50	20	0.36
	21	69	63.908	12	13	32	53	20	0.40
	22	72	66.929	12	13	35	56	20	0.45
	23	75	69.951	15	16	38	59	20	0.49
	24	78	72.974	15	16	40	62	20	0.54
	25	81	75.997	15	16	42	65	20	0.59
	26	84	79.022	15	16	45	68	20	0.60
	27	87	82.046	15	16	48	71	20	0.69
28	90	85.072	15	16	50	74	20	0.75	
30	96	91.124	15	16	52	80	20	0.87	