



# 40SD


## SD Single-Double Sprocket

### Order Product Code

**40SD 20**



- Chain ..... **No.40**
- Chain Pitch ..... (P) **12.70 mm**
- Roller Link Inner Width ..... (W) **7.95 mm**
- Roller Outside Diameter ..... (Dr) **7.92 mm**
- Tooth Width ..... (T) **7.2 mm (C) 27.8 mm**



Use together with the KANA machine key. Refer to P.334 to P.335

- m** Carbon Structural Steel
- h** High-frequency Hardened Teeth

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d			BD	BL	Weight kg
				Prepared Hole	Minimum	Maximum			
40SD	10	47	41.098	10	11	15	25	35	0.20
	11	51	45.078	10	11	16	30	35	0.27
	12	55	49.069	10	11	18	34	35	0.33
	13	59	53.068	13	14	20	38	35	0.40
	14	63	57.073	13	14	25	42	35	0.49
	15	67	61.084	13	14	28	46	35	0.57
	16	71	65.098	13	14	30	50	35	0.66
	17	76	69.116	13	14	32	54	35	0.76
	18	80	73.136	13	14	38	59	35	0.89
	19	84	77.159	13	14	42	63	35	1.00
	20	88	81.184	13	14	45	67	35	1.14
	21	92	85.211	13	14	48	71	35	1.23
	22	96	89.239	13	14	50	75	35	1.38
	23	100	93.268	13	14	52	78	35	1.51
	24	104	97.298	13	14	55	83	35	1.68
	25	108	101.330	13	14	58	87	35	1.84
	26	112	105.362	13	14	62	92	35	2.02
	27	116	109.395	16	17	65	96	35	2.04
	28	120	113.429	16	17	68	100	35	2.22
	29	124	117.463	16	17	70	104	35	2.56
	30	128	121.498	16	17	75	108	35	2.75