


410A

Order Product Code

410A 15
 TYPE No. of Teeth
 Sprocket No.



- ChainNo.410
- Chain Pitch(P) 12.70mm
- Roller Link Inner Width(W) 3.40mm
- Roller Outside Diameter(Dr) 7.75mm
- Tooth Width(T) 2.8 mm

m Common Steel

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		Weight kg
				Prepared Hole	Minimum	
410A	8	39	33.187	8	9	0.01
	9	43	37.132	8	9	0.02
	10	47	41.098	9	10	0.05
	11	51	45.078	10	11	0.09
	12	55	49.069	10	11	0.10
	13	59	53.068	12	13	0.12
	14	63	57.073	12	13	0.14
	15	67	61.084	12	13	0.16
	16	71	65.098	13	14	0.18
	17	76	69.116	13	14	0.20
	18	80	73.136	13	14	0.23
	19	84	77.159	13	14	0.26
	20	88	81.184	14	15	0.29
	21	92	85.211	14	15	0.30
	22	96	89.239	14	15	0.35
	23	100	93.268	14	15	0.38
	24	104	97.298	14	15	0.40
	25	108	101.330	14	15	0.45
	26	112	105.362	14	15	0.49
	27	116	109.395	14	15	0.50
	28	120	113.429	14	15	0.56
	29	124	117.463	14	15	0.60
	30	128	121.498	14	15	0.63
	31	133	125.533	14	15	0.65
	32	137	129.569	14	15	0.70

Standard Sprocket A-type

m Common Steel

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		Weight kg
				Prepared Hole	Minimum	
410A	33	141	133.605	14	15	0.75
	34	145	137.642	14	15	0.80
	35	149	141.679	14	15	0.85
	36	153	145.716	16	17	0.90
	37	157	149.754	16	17	0.99
	38	161	153.791	16	17	1.00
	39	165	157.830	16	17	1.15
	40	169	161.868	16	17	1.20
	41	173	165.906	16	17	1.20
	42	177	169.945	16	17	1.25
	44	185	178.023	16	17	1.35
	45	189	182.062	16	17	1.40
	46	193	186.101	16	17	1.49
	47	197	190.141	16	17	1.58
	48	201	194.180	16	17	1.63
	49	205	198.220	16	17	1.73
50	209	202.260	16	17	1.80	
52	218	210.340	16	17	1.93	
54	226	218.420	16	17	2.00	
60	250	242.663	16	17	2.60	