


50SD

SD Single-Double Sprocket


Order Product Code

50SD 15

TYPE No. of Teeth
Sprocket No.



- Chain **No.50**
- Chain Pitch **(P) 15.875mm**
- Roller Link Inner Width ... **(W) 9.53 mm**
- Roller Outside Diameter ... **(Dr) 10.16 mm**
- Tooth Width **(T) 8.7 mm (C) 31.3mm**



Use together with the KANA machine key. Refer to P.334 to P.335

- m** Carbon Structural Steel
- h** High-frequency Hardened Teeth

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d			BD	BL	Weight kg
				Prepared Hole	Minimum	Maximum			
50SD	10	58	51.373	13	14	18	32	40	0.40
	11	64	56.348	13	14	20	37	40	0.52
	12	69	61.336	13	14	25	43	40	0.63
	13	74	66.335	13	14	28	48	40	0.75
	14	79	71.342	13	14	32	53	40	0.90
	15	84	76.355	13	14	35	58	40	1.04
	16	89	81.373	13	14	42	63	40	1.22
	17	94	86.395	13	14	45	68	40	1.41
	18	100	91.420	13	14	48	73	40	1.61
	19	105	96.449	16	17	52	79	40	1.80
	20	110	101.480	16	17	57	84	40	1.95
	21	115	106.513	16	17	60	89	40	2.27
	22	120	111.548	16	17	62	92	40	2.46
	23	125	116.585	16	17	68	99	40	2.77
	24	130	121.623	16	17	70	102	40	2.98
	25	135	126.662	16	17	75	109	40	3.32
	26	140	131.703	18	19	78	115	40	3.66
	27	145	136.744	18	19	82	120	40	3.97
	28	150	141.786	18	19	85	125	40	4.29
	29	155	146.829	18	19	90	130	40	4.62
30	161	151.873	18	19	96	136	40	5.00	