


# 60A

## Order Product Code

### 60A 20

TYPE No. of Teeth  
Sprocket No.



- Chain ..... **No.60**
- Chain Pitch ..... **(P) 19.05 mm**
- Roller Link Inner Width ..... **(W) 12.70 mm**
- Roller Outside Diameter ..... **(Dr) 11.91 mm**
- Tooth Width ..... **(T) 11.7 mm**

**m** Common Steel

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		Weight kg
				Prepared Hole	Minimum	
<b>60A</b>	10	70	61.647	14	15	0.27
	11	76	67.617	14	15	0.30
	12	83	73.604	14	15	0.38
	13	89	79.602	14	15	0.45
	14	95	85.610	16	17	0.50
	15	101	91.625	16	17	0.60
	16	107	97.647	16	17	0.65
	17	113	103.674	16	17	0.75
	18	119	109.705	16	17	0.84
	19	126	115.739	16	17	0.93
	20	132	121.776	16	17	1.05
	21	138	127.816	16	17	1.15
	22	144	133.858	16	17	1.25
	23	150	139.902	16	17	1.40
	24	156	145.948	18	19	1.50
	25	162	151.995	18	19	1.62
	26	168	158.043	18	19	1.78
	27	174	164.093	18	19	1.90
	28	180	170.143	18	19	2.05
	29	187	176.195	18	19	2.20
	30	193	182.247	18	19	2.35
	31	199	188.300	20	21	2.50
	32	205	194.354	20	21	2.68
	33	211	200.408	20	21	2.85
	34	217	206.463	20	21	3.02
	35	223	212.518	20	21	3.25
	36	229	218.574	20	21	3.40

# Standard Sprocket A-type

**m** Common Steel

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		Weight kg
				Prepared Hole	Minimum	
60A	37	235	224.631	20	21	3.60
	38	241	230.687	20	21	3.80
	39	247	236.744	20	21	4.00
	40	253	242.802	20	21	4.20
	41	260	248.859	20	21	4.45
	42	266	254.917	20	21	4.63
	43	272	260.976	20	21	4.85
	44	278	267.034	20	21	5.10
	45	284	273.093	20	21	5.30
	46	290	279.152	20	21	5.59
	47	296	285.211	20	21	5.83
	48	302	291.270	20	21	6.10
	49	308	297.330	20	21	6.34
	50	314	303.390	20	21	6.60
	51	320	309.450	20	21	6.87
	52	326	315.510	20	21	7.15
	53	332	321.570	20	21	7.44
	54	338	327.630	20	21	7.70
	55	345	333.691	20	21	8.00
	57	357	345.812	20	21	8.59
	58	363	351.873	20	21	8.90
60	375	363.994	20	21	9.50	
65	405	394.301	26	27	11.20	
70	436	424.609	26	27	13.00	
72	448	436.732	26	27	13.70	
75	466	454.918	26	27	14.90	
80	496	485.229	26	27	16.90	
90	557	545.853	26	27	21.40	