




# 60SD

## SD Single-Double Sprocket

### Order Product Code



Use together with the KANA machine key. Refer to P.334 to P.335

- Chain ..... **No.60**
- Chain Pitch ..... **(P) 19.05 mm**
- Roller Link Inner Width ..... **(W) 12.70 mm**
- Roller Outside Diameter ..... **(Dr) 11.91 mm**
- Tooth Width ..... **(T) 11.7 mm (C) 38.3mm**

- **m** Carbon Structural Steel
- **h** High-frequency Hardened Teeth

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d			BD	BL	Weight kg
				Prepared Hole	Minimum	Maximum			
<b>60SD</b>	10	70	61.647	13	14	20	37	50	0.74
	11	76	67.617	13	14	26	45	50	0.92
	12	83	73.604	13	14	32	51	50	1.14
	13	89	79.602	16	17	35	57	50	1.39
	14	95	85.610	16	17	42	64	50	1.63
	15	101	91.625	16	17	46	70	50	1.96
	16	107	97.647	16	17	51	76	50	2.20
	17	113	103.674	16	17	55	82	50	2.56
	18	119	109.705	18	19	60	88	50	2.90
	19	126	115.739	18	19	63	94	50	3.26
	20	132	121.776	18	19	68	100	50	3.70
	21	138	127.816	18	19	75	107	50	4.13
	22	144	133.858	18	19	78	113	50	4.59
	23	150	139.902	20	21	82	119	50	5.03
	24	156	145.948	20	21	85	125	50	5.52
	25	162	151.995	20	21	90	130	50	5.99
	26	168	158.043	20	21	96	138	50	6.64
	27	174	164.093	20	21	100	144	50	7.20
	28	180	170.143	20	21	106	150	50	7.78
	29	187	176.195	20	21	110	157	50	8.43
	30	193	182.247	20	21	114	163	50	9.06