表面処理





ご注文方法 商品コード FBN120B13D45

i I I B D H7 TYPE

BK UC вк

黒染(四三酸化鉄被膜)






■チェーン ···········No.120

■ローラリンク内幅 ······(W)25.40mm

■ローラ外径 ······(Dr)22.23mm ■歯幅······(T)24.0(最大) mm



m 機械構造用炭素鋼

h 歯先高周波焼入

	() = 110(121) () 11111											
ТҮРЕ	歯数	外径 Do	ピッチ径 Dp	ボス径 BD	ボス長さ BL	a	重量 kg	φ D ^{H7}	定価(円)	φ D ^{H7}	定価(円)	歯数
	12	165	147.207	98	56	16	4.8	65	18,900			12
	13	177	159.204	98	56	16	5.3	45 48 50	24,300	55 60 63	25,200	13
	14	190	171.220	107	56	16	6.3	45 48 50	26,700	55 60 65 70	28,100	14
	15	202	183.251	117	63	16	7.8	45 48 50	28,300	55 60 65 70	31,200	15
	16	214	195.294	117	63	16	8.4	50 60 70	33,200			16
FBN	17	227	207.347	117	63	16	9.1	60 70	35,700			17
	18	239	219.409	117	63	16	9.9	50 60 70	36,400			18
120B	19	251	231.478	117	63	16	10.7	50 60	40,900			19
	20	263	243.552	127	63	16	12.1	50 60 70 80	43,100			20
	21	276	255.632	127	63	16	13.0	50 60	43,800			21
	24	312	291.895	127	63	16	15.2	80	53,500			24
	25	324	303.990	127	63	16	16.2	70	54,800			25
	30	385	364.494	137	71	16	23.2	70	78,700			30

軸穴加工仕椅

ŧ	φ D ^{H7}	キー溝 b×t²	セット スクリューM		
	45~50	14×3.8	10		
	55	16×4.3	12		
	60~65	18×4.4	12		
	70	20×4.9	16		
	80	22×5.4	16		