




KANA FBN50SD



●ご注文方法 商品コード FBN50SD20D40

TYPE 歯数 ϕD^{H7}

- チェーン No.50
- チェーンピッチ (P) 15.875mm
- ローラリンク内幅 (W) 9.53 mm
- ローラ外径 (Dr) 10.16 mm
- 歯幅 (T) 8.9(最大) mm
(C) 31.1(最小) mm



m 機械構造用炭素鋼
h 歯先高周波焼入

TYPE	歯数	外径 Do	ピッチ径 Dp	ボス径 BD	ボス長さ BL	a	質量 (kg)	ϕD^{H7}				定価 (円)	歯数		
FBN 50SD	12	69	61.336	43	40	20	0.63	18	20	25		3,300	12		
	13	74	66.335	48	40	20	0.75	20	25	28	30	2,900	13		
	14	79	71.342	53	40	20	0.90	20	25	28	30	3,300	14		
	15	84	76.355	58	40	20	1.04	20	25	28	30	35	3,400	15	
	16	89	81.373	63	40	20	1.22	25	28	30	35	38	40	4,100	16
	17	94	86.395	68	40	20	1.41	25	28	30	35	40	4,400	17	
	18	100	91.420	73	40	20	1.61	25	28	30	35	40	4,600	18	
	19	105	96.449	79	40	20	1.80	25	28	30	35	40	5,100	19	
	20	110	101.480	84	40	20	1.95	25	28	30	35	40	5,000	20	
	21	115	106.513	89	40	20	2.27	28	30	35	40		5,500	21	

軸穴加工仕様

ϕD^{H7}	キ一溝 $b \times t^2$	セット スクリューM
18~22	6×2.8	6
24~30	8×3.3	8
32~38	10×3.3	8
40	12×3.3	8