


HG100-2A

HG High-grade Sprocket with Hardened Teeth Two-row A-type

Order Product Code

HG100-2A 22H

TYPE No. of Teeth
Sprocket No.



- Chain **No.100-2**
- Chain Pitch **(P) 31.75mm**
- Roller Link Inner Width ... **(W) 19.05mm**
- Roller Outside Diameter ... **(Dr) 19.05mm**
- Tooth Width **(T) 17.0 mm**
- Complete Tooth Width ... **(M) 52.8 mm**

m Carbon Structural Steel

h High-frequency Hardened Teeth

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		DH	M	Shape	Weight kg
				Prepared Hole	Minimum				
HG100-2A	22H	240	223.097	28	29	188	52.8	Ground Specification	14.17
	23H	250	233.170	28	29	199	52.8		15.62
	24H	260	243.246	33	34	209	52.8		17.11
	25H	270	253.325	33	34	219	52.8		18.65
	26H	281	263.405	33	34	229	52.8		20.25
	27H	291	273.488	33	34	239	52.8		21.93
	28H	301	283.572	33	34	249	52.8		23.67
	30H	321	303.745	33	34	270	52.8		27.41
	32H	341	323.923	33	34	290	52.8		31.35
	33H	352	334.013	33	34	300	52.8		33.41
	34H	362	344.105	33	34	310	52.8		35.55
	35H	372	354.197	33	34	320	52.8		37.76
	36H	382	364.290	33	34	330	52.8		40.02
	40H	422	404.669	33	34	371	52.8		49.84
	45H	473	455.155	33	34	422	52.8		63.59
	48H	503	485.451	33	34	452	52.8		72.58
	50H	524	505.650	33	34	472	52.8		78.90
	60H	625	606.657	33	34	573	52.8		114.60