



HG100-2B



HG High-grade Sprocket with Hardened Teeth Two-row B-type

● Order No. Example

HG100-2B 18H



- ChainNo.100-2
- Chain Pitch(P)31.75mm
- Roller Link Inner Width(W)19.05mm
- Roller Outside Diameter(Dr)19.05mm
- Tooth Width(T)17.0 mm (M)52.8mm

m Carbon Structural Steel

h High-frequency Hardened Teeth

Type	No. of Teeth	Outer Diameter Do	Pitch Diameter Dp	Shaft Hole Diameter d	Boss Diameter BD	Boss Length BL	Shape	Weight kg	¥	Semi-F ¥
HG 100-2B	15H	168	152.71	28	29	80	Ground Specification	7.10		
	16H	179	162.74	28	29	89		7.70		
	17H	189	172.79	28	29	89		8.90		
	18H	199	182.84	28	29	89		9.60		
	19H	209	192.90	28	29	89		12.80		
	20H	220	202.96	28	29	89		13.50		
	21H	230	213.03	28	29	89		14.30		



Order Method

Sprocket No. and Quantity



Guide

* Since we also manufacture sizes other than those in the catalog, and machine shaft holes/keys/taps, etc., depending on your request, please contact our company's sales office for details.



Postage

Same-day shipping

* Please refer to P24 to P33 for the Semi-F Series <Complete Product> order method.