



# HG120-2B



## HG High-grade Sprocket with Hardened Teeth Two-row B-type

### Order No. Example

**HG120-2B 18H**



- Chain .....No.120-2
- Chain Pitch .....(P)38.10mm
- Roller Link Inner Width .....(W)25.40mm
- Roller Outside Diameter .....(Dr)22.23mm
- Tooth Width .....(T)22.7 mm (M)68.1mm

**m** Carbon Structural Steel

**h** High-frequency Hardened Teeth

Type	No. of Teeth	Outer Diameter Do	Pitch Diameter Dp	Shaft Hole Diameter d			Boss Diameter BD	Boss Length BL	Shape	Weight kg	¥	Semi-F ¥
				Prepared Hole Product	Minimum	Maximum						
HG 120-2B	14H	190	171.22	28	29	80	120	100	Ground Specification	11.40		
	15H	202	183.25	33	34	80	120	100		13.20		
	16H	214	195.29	33	34	95	140	100		16.50		
	17H	227	207.35	33	34	95	140	100		19.00		
	18H	239	219.41	33	34	103	150	100		21.00		
	19H	251	231.48	33	34	103	150	100		23.00		
	20H	263	243.55	33	34	103	150	100		26.00		
	21H	276	255.63	33	34	103	150	100		28.00		



Sprocket No. and Quantity



Same-day shipping



\* Since we also manufacture sizes other than those in the catalog, and machine shaft holes/keys/taps, etc., depending on your request, please contact our company's sales office for details.

\* Please refer to P24 to P33 for the Semi-F Series <Complete Product> order method.