



HG120A

Order Product Code

HG120A 20H



- Chain **No.120**
- Chain Pitch **(P) 38.10 mm**
- Roller Link Inner Width **(W) 25.40 mm**
- Roller Outside Diameter **(Dr) 22.23 mm**
- Tooth Width **(T) 23.5 mm**

m Carbon Structural Steel

h High-frequency Hardened Teeth

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		Weight kg
				Prepared Hole	Minimum	
HG120A	10H	140	123.294	23	24	2.16
	11H	153	135.235	25	26	2.60
	12H	165	147.207	25	26	3.10
	13H	177	159.204	25	26	3.60
	14H	190	171.220	25	26	4.20
	15H	202	183.251	25	26	4.80
	16H	214	195.294	25	26	5.50
	17H	227	207.347	25	26	6.20
	18H	239	219.409	25	26	6.95
	19H	251	231.478	25	26	7.70
	20H	263	243.552	25	26	8.55
	21H	276	255.632	25	26	9.40
	22H	288	267.716	26	27	10.30
	23H	300	279.804	26	27	11.30
	24H	312	291.895	26	27	12.30
	25H	324	303.990	26	27	13.30
	26H	337	316.086	26	27	14.40
	27H	349	328.185	26	27	15.50
	28H	361	340.287	26	27	16.70
	29H	373	352.389	26	27	17.80

HG High-grade Sprocket with Hardened Teeth A-type

m Carbon Structural Steel

h High-frequency Hardened Teeth

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		Weight kg
				Prepared Hole	Minimum	
HG120A	30H	385	364.494	26	27	19.20
	32H	410	388.708	30	31	21.80
	34H	434	412.926	30	31	24.60
	35H	446	425.037	30	31	26.10
	36H	458	437.148	30	31	27.60
	38H	483	461.374	30	31	30.80
	40H	507	485.603	30	31	34.10
	42H	531	509.835	30	31	37.60
	44H	556	534.068	30	31	41.20
	45H	568	546.186	30	31	43.10
	46H	580	558.304	30	31	45.10
	48H	604	582.541	30	31	49.00
	50H	628	606.779	30	31	53.30
	52H	653	631.019	30	31	57.70
	54H	677	655.260	30	31	62.10
	55H	689	667.381	30	31	69.40
	60H	750	727.989	30	31	76.70
65H	811	788.601	30	31	90.50	
70H	871	849.218	30	31	104.30	
75H	932	909.837	30	31	119.80	