



HG140A

HG High-grade Sprocket with Hardened Teeth A-type

Order Product Code

HG140A 20H



- Chain **No.140**
- Chain Pitch **(P) 44.45 mm**
- Roller Link Inner Width **(W) 25.40 mm**
- Roller Outside Diameter **(Dr) 25.40 mm**
- Tooth Width **(T) 23.5 mm**

- **m** Carbon Structural Steel
- **h** High-frequency Hardened Teeth

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		Weight kg
				Prepared Hole	Minimum	
HG140A	10H	163	143.843	26	27	2.90
	11H	178	157.774	26	27	3.60
	12H	193	171.742	26	27	4.20
	13H	207	185.738	26	27	4.90
	14H	221	199.756	26	27	5.70
	15H	236	213.793	26	27	6.60
	16H	250	227.843	26	27	7.50
	17H	264	241.905	26	27	8.40
	18H	279	255.977	26	27	9.40
	19H	293	270.057	26	27	10.50
	20H	307	284.145	26	27	11.60
	21H	322	298.238	26	27	12.80
	22H	336	312.336	30	31	14.10
	23H	350	326.438	30	31	15.30
	24H	364	340.545	30	31	16.70
	25H	379	354.655	30	31	18.10
	26H	393	368.767	30	31	19.60
	27H	407	382.883	30	31	21.20
	28H	421	397.001	30	31	22.80
	30H	450	425.243	30	31	26.00
	32H	478	453.492	30	31	29.70
	35H	521	495.876	30	31	35.60
	38H	563	538.270	30	31	41.90
	40H	591	566.537	30	31	46.40
	45H	662	637.217	30	31	58.80
	48H	705	679.631	30	31	66.90
	50H	733	707.909	30	31	72.50
	60H	875	849.320	35	36	104.00