


HG160-2A

HG High-grade Sprocket with Hardened Teeth Two-row A-type

● Order Product Code

HG160-2A 18H

TYPE No. of Teeth
 Sprocket No.



- Chain **No.160-2**
- Chain Pitch **(P) 50.80 mm**
- Roller Link Inner Width **(W) 31.75 mm**
- Roller Outside Diameter **(Dr) 28.58 mm**
- Tooth Width **(T) 28.4 mm**
- Complete Tooth Width **(M) 86.9 mm**

- **m** Carbon Structural Steel
- **h** High-frequency Hardened Teeth

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		DH	M	Shape	Weight kg
				Prepared Hole	Minimum				
HG160-2A	13H	237	212.272	38	39	155	86.9	Ground Specification	19.67
	14H	253	228.293	38	39	171	86.9		23.10
	15H	269	244.335	38	39	187	86.9		26.81
	16H	286	260.392	38	39	204	86.9		30.87
	17H	302	276.463	38	39	220	86.9		35.14
	18H	319	292.546	38	39	237	86.9		39.78
	19H	335	308.637	38	39	253	86.9		44.61
	20H	351	324.737	38	39	269	86.9		49.71
	21H	368	340.843	38	39	285	86.9		55.10
	22H	384	356.955	38	39	302	86.9		60.88
26H	449	421.448	38	39	367	86.9	86.46		
30H	514	485.992	38	39	432	86.9	116.53		