



HG160A

HG High-grade Sprocket with Hardened Teeth A-type

Order Product Code

HG160A 20H



- Chain **No.160**
- Chain Pitch **(P) 50.80 mm**
- Roller Link Inner Width **(W) 31.75 mm**
- Roller Outside Diameter **(Dr) 28.58 mm**
- Tooth Width **(T) 29.4 mm**

- **m** Carbon Structural Steel
- **h** High-frequency Hardened Teeth

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		Weight kg
				Prepared Hole	Minimum	
HG160A	10H	187	164.392	26	27	4.85
	11H	204	180.313	26	27	5.85
	12H	220	196.276	26	27	6.90
	13H	237	212.272	26	27	8.10
	14H	253	228.293	26	27	9.40
	15H	269	244.335	30	31	10.80
	16H	286	260.392	30	31	12.25
	17H	302	276.463	30	31	13.80
	18H	319	292.546	30	31	15.50
	19H	335	308.637	30	31	17.20
	20H	351	324.737	30	31	19.00
	21H	368	340.843	30	31	21.00
	22H	384	356.955	35	36	23.00
	23H	400	373.072	35	36	25.10
	24H	416	389.194	35	36	27.40
	25H	433	405.319	35	36	29.70
	26H	449	421.448	35	36	32.10
	27H	465	437.581	35	36	34.80
	28H	481	453.715	35	36	37.30
	30H	514	485.992	35	36	42.70
	32H	546	518.277	35	36	48.70
	35H	595	566.716	35	36	58.10
	38H	644	615.166	35	36	68.50
	40H	676	647.471	35	36	75.10
	45H	757	728.248	35	36	96.00
	48H	806	776.721	35	36	109.00
	50H	838	809.039	35	36	118.50
	60H	1,000	970.652	35	36	170.00