


# HG180A

## HG High-grade Sprocket with Hardened Teeth A-type

### ● Order Product Code

**HG180A 20H**

TYPE	No. of Teeth
Sprocket No.	



- Chain ..... **No.180**
- Chain Pitch ..... **(P) 57.15 mm**
- Roller Link Inner Width ..... **(W) 35.72 mm**
- Roller Outside Diameter ..... **(Dr) 35.71 mm**
- Tooth Width ..... **(T) 33 mm**

m Carbon Structural Steel

h High-frequency Hardened Teeth

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		Weight kg
				Prepared Hole	Minimum	
<b>HG180A</b>	12H	248	220.811	35	36	9.90
	14H	285	256.830	35	36	13.39
	15H	303	274.876	35	36	15.33
	16H	322	292.941	35	36	17.42
	17H	340	311.021	35	36	19.63
	18H	358	329.114	35	36	21.98
	20H	395	365.329	35	36	27.09
	21H	413	383.448	35	36	29.84
	22H	432	401.574	35	36	32.73
	24H	468	437.843	35	36	38.91
	25H	487	455.984	35	36	42.20
	30H	578	546.741	35	36	60.67
	32H	615	583.061	35	36	68.99
	35H	669	637.555	35	36	82.50
38H	724	692.062	35	36	97.20	