



HG200A

HG High-grade Sprocket with Hardened Teeth A-type

Order Product Code

HG200A 20H



- Chain **No.200**
- Chain Pitch **(P) 63.50 mm**
- Roller Link Inner Width **(W) 38.10 mm**
- Roller Outside Diameter **(Dr) 39.68 mm**
- Tooth Width **(T) 35.3 mm**

- **m** Carbon Structural Steel
- **h** High-frequency Hardened Teeth

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		Weight kg
				Prepared Hole	Minimum	
HG200A	11H	254	225.391	35	36	10.70
	12H	275	245.345	35	36	12.80
	13H	296	265.340	35	36	15.00
	14H	316	285.366	35	36	17.40
	15H	337	305.418	35	36	20.00
	16H	357	325.490	35	36	22.70
	17H	378	345.579	35	36	25.80
	18H	398	365.682	35	36	28.90
	19H	419	385.796	35	36	32.10
	20H	439	405.921	35	36	35.60
	21H	459	426.054	35	36	39.20
	22H	480	446.194	35	36	43.00
	24H	520	486.492	35	36	51.10
	25H	541	506.649	35	36	55.60
	26H	561	526.811	35	36	60.10
	28H	602	567.144	35	36	69.70
	30H	642	607.490	35	36	79.90
	32H	683	647.846	35	36	91.10
	35H	744	708.395	35	36	109.00
	40H	845	809.339	35	36	142.00
45H	946	910.310	40	41	180.00	