



HG40A

Order Product Code

HG40A 20H



- Chain **No.40**
- Chain Pitch **(P) 12.70 mm**
- Roller Link Inner Width **(W) 7.95 mm**
- Roller Outside Diameter **(Dr) 7.92 mm**
- Tooth Width **(T) 7.2 mm**

m Carbon Structural Steel

h High-frequency Hardened Teeth

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		Weight kg
				Prepared Hole	Minimum	
HG40A	11H	51	45.078	10	11	0.09
	12H	55	49.069	10	11	0.10
	13H	59	53.068	12	13	0.12
	14H	63	57.073	12	13	0.14
	15H	67	61.084	12	13	0.16
	16H	71	65.098	13	14	0.18
	17H	76	69.116	13	14	0.20
	18H	80	73.136	13	14	0.23
	19H	84	77.159	14	15	0.26
	20H	88	81.184	14	15	0.29
	21H	92	85.211	14	15	0.30
	22H	96	89.239	14	15	0.35
	23H	100	93.268	14	15	0.38
	24H	104	97.298	14	15	0.40
	25H	108	101.330	14	15	0.45
	26H	112	105.362	14	15	0.49
	27H	116	109.395	14	15	0.50
	28H	120	113.429	14	15	0.56
	29H	124	117.463	14	15	0.60
	30H	128	121.498	14	15	0.63

HG High-grade Sprocket with Hardened Teeth A-type

m Carbon Structural Steel

h High-frequency Hardened Teeth

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		Weight kg
				Prepared Hole	Minimum	
HG40A	32H	137	129.569	14	15	0.70
	34H	145	137.642	14	15	0.80
	35H	149	141.679	14	15	0.85
	36H	153	145.716	16	17	0.90
	38H	161	153.791	16	17	1.00
	40H	169	161.868	16	17	1.20
	42H	177	169.945	16	17	1.25
	44H	185	178.023	16	17	1.35
	45H	189	182.062	16	17	1.40
	46H	193	186.101	16	17	1.49
	48H	201	194.180	16	17	1.63
	50H	209	202.260	16	17	1.80
	52H	218	210.340	16	17	1.93
	54H	226	218.420	16	17	2.00
	55H	230	222.460	16	17	2.18
	60H	250	242.663	16	17	2.60
65H	270	262.867	16	17	3.00	
70H	290	283.073	16	17	3.50	
80H	331	323.486	20	21	4.60	