



HG50-2B



HG High-grade Sprocket with Hardened Teeth Two-row B-type

Order No. Example

HG50-2B 26H



- Chain No.50-2
 - Chain Pitch (P)15.875mm
 - Roller Link Inner Width (W) 9.53 mm
 - Roller Outside Diameter (Dr)10.16 mm
 - Tooth Width (T) 8.4 mm (M)26.5mm
- m Carbon Structural Steel
h High-frequency Hardened Teeth

| Type | No. of Teeth | Outer Diameter Do | Pitch Diameter Dp | Shaft Hole Diameter d | | | Boss Diameter BD | Boss Length BL | Shape | Weight kg | ¥ | Semi-F ¥ |
|---------------------------|--------------|-------------------|-------------------|-----------------------|---------|---------|------------------|----------------|----------------------|-----------|---|----------|
| | | | | Prepared Hole Product | Minimum | Maximum | | | | | | |
| HG 50-2B | 26H | 140 | 131.70 | 18 | 19 | 70 | 105 | 50 | Ground Specification | 4.50 | | |
| | 27H | 145 | 136.74 | 18 | 19 | 70 | 105 | 50 | | 4.80 | | |
| | 28H | 150 | 141.79 | 18 | 19 | 75 | 110 | 50 | | 5.10 | | |
| | 30H | 161 | 151.87 | 18 | 19 | 80 | 120 | 50 | | 5.80 | | |



Sprocket No. and Quantity



* Since we also manufacture sizes other than those in the catalog, and machine shaft holes/keys/taps, etc., depending on your request, please contact our company's sales office for details.



Same-day shipping

* Please refer to P24 to P33 for the Semi-F Series <Complete Product> order method.