



HG80-2A

HG High-grade Sprocket with Hardened Teeth Two-row A-type

● Order Product Code

HG80-2A 22H

- Chain **No.80-2**
- Chain Pitch **(P) 25.4 mm**
- Roller Link Inner Width **(W) 15.88 mm**
- Roller Outside Diameter **(Dr) 15.88 mm**
- Tooth Width **(T) 14.1 mm**
- Complete Tooth Width **(M) 43.4 mm**

m Carbon Structural Steel

h High-frequency Hardened Teeth

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		DH	M	Shape	Weight kg
				Prepared Hole	Minimum				
HG80-2A	22H	192	178.478	23	24	150	43.4	Ground Specification	7.49
	23H	200	186.536	23	24	159	43.4		8.28
	24H	208	194.597	23	24	167	43.4		9.04
	25H	216	202.660	23	24	175	43.4		9.88
	26H	224	210.724	23	24	183	43.4		10.73
	27H	233	218.790	23	24	191	43.4		11.61
	28H	241	226.858	23	24	199	43.4		12.57
	30H	257	242.996	23	24	215	43.4		14.55
	32H	273	259.138	28	29	232	43.4		16.66
	35H	297	283.358	28	29	256	43.4		20.09
	36H	306	291.432	28	29	264	43.4		21.28
	38H	322	307.583	28	29	280	43.4		23.84
	40H	338	323.736	33	34	297	43.4		26.53
	42H	354	339.890	33	34	313	43.4		29.27
	44H	370	356.046	33	34	329	43.4		32.31
	45H	378	364.124	33	34	337	43.4		32.78
	46H	387	372.203	33	34	345	43.4		35.34
	48H	403	388.361	33	34	361	43.4		38.56
50H	419	404.520	33	34	378	43.4	42.05		
60H	500	485.326	33	34	459	43.4	61.04		