



HG80-2B



HG High-grade Sprocket with Hardened Teeth Two-row B-type

● Order No. Example

HG 80-2B 20H



- ChainNo.80-2
- Chain Pitch(P)25.4 mm
- Roller Link Inner Width(W)15.88mm
- Roller Outside Diameter(Dr)15.88mm
- Tooth Width(T)14.1 mm (M)43.4mm

- m Carbon Structural Steel
- h High-frequency Hardened Teeth

Type	No. of Teeth	Outer Diameter Do	Pitch Diameter Dp	Shaft Hole Diameter d			Boss Diameter BD	Boss Length BL	Shape	Weight kg	¥	Semi-F ¥
				Prepared Hole Product	Minimum	Maximum						
HG 80-2B	18H	159	146.27	23	24	80	120	71	Ground Specification	7.50		
	19H	167	154.32	23	24	80	120	71		8.00		
	20H	176	162.37	23	24	89	130	71		9.00		
	21H	184	170.42	23	24	89	130	71		10.30		

* Please refer to P24 to P33 for the Semi-F Series <Complete Product> order method.



Sprocket No. and Quantity



Same-day shipping



* Since we also manufacture sizes other than those in the catalog, and machine shaft holes/keys/taps, etc., depending on your request, please contact our company's sales office for details.