



K35B

K Sprocket Former B-type

● Order Product Code

K35B 12

TYPE No. of Teeth
Sprocket No.



- Chain **No.35**
- Chain Pitch **(P) 9.525 mm**
- Bushing Link Inner Width **(W) 4.78 mm**
- Bushing Outside Diameter **(Dr) 5.08 mm**
- Tooth Width **(T) 4.3 mm**

Use together with the KANA machine key.
Refer to P.334 to P.335

- m** Carbon Structural Steel
- h** High-frequency Hardened Teeth

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d			BD	BL	Shape	Weight kg	
				Prepared Hole	Minimum	Maximum					
K35B	10	35	30.824	8	9	10	20	20	Ground Specification	0.06	
	11	38	33.809	8	9	10	20	20		0.08	
	12	41	36.802	9	10	14	27	20		0.09	
	13	44	39.801	9	10	14	27	20		0.10	
	14										
	15										
	16										
	17										
	18										
	19										
	20										
	21										
	22										
	23										
	24	78	72.974	11	12	38	60	25	Ground Specification	0.59	
	25	81	75.997	11	12	38	60	25		0.60	
	26	84	79.022	11	12	38	60	25		0.60	
	28	90	85.072	11	12	38	60	25		0.62	
	30	96	91.124	11	12	38	60	25		0.65	
	33	105	100.204	11	12	38	60	25		Ground Specification	0.68
	37	118	112.315	12	13	35	55	35			0.91
	38	121	115.344	12	13	35	55	35			0.93
	39	124	118.372	12	13	35	55	35			0.95
	40	127	121.401	12	13	35	55	35			0.97

The dimensions for K35B14 to 23 are relocated, as they are equivalent to those of NK35B14 to 23.
Please see NK35B P.152 about this product.