



SUS35B

SUS Stainless Steel Sprocket B-type



Order Product Code

SUS35B 20



(BD marked with ★)

- Chain **No.35**
- Chain Pitch (P) **9.525 mm**
- Bushing Link Inner Width (W) **4.78 mm**
- Bushing Outside Diameter (Dr) **5.08 mm**
- Tooth Width (T) **4.3 mm**



Use together with the KANA machine key. Refer to P.334 to P.335

⚠ Sprockets with a ★ symbol for BD have a channel in the boss exterior.

No. of Teeth	S	GD
9	4.4	17
10		20
11	4.4	23
12		26
13	4.4	29

■ Stainless Steel GB 304

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d			BD	BL	Shape	Weight kg
				Prepared Hole	Minimum	Maximum				
SUS35B	9	32	27.849	8	9	11	★21.5	20	Ground Specification	0.06
	10	35	30.824	8	9	12	★24.5	20		0.08
	11	38	33.809	8	9	14	★27	20		0.09
	12	41	36.802	9	10	16	★30.5	20		0.12
	13	44	39.801	9	10	18	★32	20		0.12
	14	47	42.805	9	10	18	32	20		0.12
	15	51	45.813	9	10	20	35	20		0.16
	16	54	48.824	9	10	20	37	20		0.19
	17	57	51.837	11	12	25	41	20		0.22
	18	60	54.852	11	12	25	44	20		0.25
	19	63	57.869	11	12	28	47	20		0.28
	20	66	60.888	11	12	30	50	20		0.32
	21	69	63.908	11	12	32	53	20		0.36
	22	72	66.929	11	12	35	56	20		0.37
	23	75	69.951	11	12	38	60	20		0.38
	24	78	72.974	11	12	32	53	22		0.43
	25	81	75.997	11	12	32	53	22		0.44
	26	84	79.022	11	12	32	53	22		0.45
	27	87	82.046	11	12	32	53	22		0.46
	28	90	85.072	11	12	32	53	22		0.48
30	96	91.124	11	12	32	53	22	0.51		
32	102	97.177	11	12	32	53	22	0.54		
34	109	103.231	11	12	32	53	22	0.57		
35	112	106.259	11	12	32	53	22	0.59		
36	115	109.287	12	13	32	53	22	0.61		
38	121	115.344	12	13	42	63	25	0.82		
40	127	121.401	12	13	42	63	25	0.85		