


SUS40A

● Order Product Code

SUS40A 20

TYPE No. of Teeth
Sprocket No.



- Chain **No.40**
- Chain Pitch **(P) 12.70 mm**
- Roller Link Inner Width **(W) 7.95 mm**
- Roller Outside Diameter **(Dr) 7.92 mm**
- Tooth Width **(T) 7.2 mm**

m Stainless Steel **GB** 304

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		Weight kg
				Prepared Hole	Minimum	
SUS40A	10	47	41.098	9	10	0.05
	11	51	45.078	10	11	0.09
	12	55	49.069	10	11	0.10
	13	59	53.068	12	13	0.12
	14	63	57.073	12	13	0.14
	15	67	61.084	12	13	0.16
	16	71	65.098	13	14	0.18
	17	76	69.116	13	14	0.20
	18	80	73.136	13	14	0.23
	19	84	77.159	14	15	0.26
	20	88	81.184	14	15	0.29
	21	92	85.211	14	15	0.30
	22	96	89.239	14	15	0.35
	23	100	93.268	14	15	0.38
	24	104	97.298	14	15	0.40

Stainless Steel Sprocket A-type

m Stainless Steel **GB** 304

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		Weight kg
				Prepared Hole	Minimum	
SUS40A	25	108	101.330	14	15	0.45
	26	112	105.362	14	15	0.49
	27	116	109.395	14	15	0.50
	28	120	113.429	14	15	0.56
	29	124	117.463	14	15	0.60
	30	128	121.498	14	15	0.63
	31	133	125.533	14	15	0.65
	32	137	129.569	14	15	0.70
	33	141	133.605	14	15	0.75
	34	145	137.642	14	15	0.80
	35	149	141.679	14	15	0.85
	36	153	145.716	16	17	0.90
	37	157	149.754	16	17	0.99
	38	161	153.791	16	17	1.00
	39	165	157.830	16	17	1.15
	40	169	161.868	16	17	1.20