


# SUS50A

## Order Product Code

### SUS50A 20

TYPE      No. of Teeth  
-----  
Sprocket No.



- Chain ..... **No.50**
- Chain Pitch ..... (P) **15.875mm**
- Roller Link Inner Width ... (W) **9.53 mm**
- Roller Outside Diameter ... (Dr) **10.16 mm**
- Tooth Width ..... (T) **8.7 mm**

**m** Stainless Steel **GB** 304

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		Weight kg
				Prepared Hole	Minimum	
<b>SUS50A</b>	10	58	51.373	10	11	0.14
	11	64	56.348	12	13	0.17
	12	69	61.336	12	13	0.20
	13	74	66.335	12	13	0.23
	14	79	71.342	12	13	0.27
	15	84	76.355	12	13	0.30
	16	89	81.373	14	15	0.35
	17	94	86.395	14	15	0.40
	18	100	91.420	14	15	0.45
	19	105	96.449	14	15	0.48
	20	110	101.480	14	15	0.50
	21	115	106.513	14	15	0.60
	22	120	111.548	16	17	0.66
	23	125	116.585	16	17	0.72
24	130	121.623	16	17	0.78	

# Stainless Steel Sprocket A-type

**m** Stainless Steel **GB** 304

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		Weight kg
				Prepared Hole	Minimum	
<b>SUS50A</b>	25	135	126.662	16	17	0.85
	26	140	131.703	16	17	0.90
	27	145	136.744	16	17	1.00
	28	150	141.786	16	17	1.05
	29	155	146.829	16	17	1.12
	30	161	151.873	16	17	1.20
	31	166	156.917	16	17	1.30
	32	171	161.961	16	17	1.35
	33	176	167.007	16	17	1.45
	34	181	172.052	16	17	1.55
	35	186	177.099	16	17	1.65
	36	191	182.145	19	20	1.75
	37	196	187.192	19	20	1.85
	38	201	192.239	19	20	1.95
	39	206	197.287	19	20	2.05
40	211	202.335	19	20	2.15	