



# SUS60A

## Order Product Code

### SUS60A 20



- Chain ..... **No.60**
- Chain Pitch ..... **(P) 19.05 mm**
- Roller Link Inner Width ..... **(W) 12.70 mm**
- Roller Outside Diameter ..... **(Dr) 11.91 mm**
- Tooth Width ..... **(T) 11.7 mm**

**m** Stainless Steel **GB** 304

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		Weight kg
				Prepared Hole	Minimum	
<b>SUS60A</b>	10	70	61.647	14	15	0.27
	11	76	67.617	14	15	0.30
	12	83	73.604	14	15	0.38
	13	89	79.602	14	15	0.45
	14	95	85.610	16	17	0.50
	15	101	91.625	16	17	0.60
	16	107	97.647	16	17	0.65
	17	113	103.674	16	17	0.75
	18	119	109.705	16	17	0.84
	19	126	115.739	16	17	0.93
	20	132	121.776	16	17	1.05
	21	138	127.816	16	17	1.15
	22	144	133.858	16	17	1.25
	23	150	139.902	16	17	1.40
	24	156	145.948	18	19	1.50
	25	162	151.995	18	19	1.62
	26	168	158.043	18	19	1.78
	27	174	164.093	18	19	1.90
	28	180	170.143	18	19	2.05
	29	187	176.195	18	19	2.20

# Stainless Steel Sprocket A-type

 Stainless Steel  304

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		Weight kg
				Prepared Hole	Minimum	
<b>SUS60A</b>	30	193	182.247	18	19	2.35
	31	199	188.300	20	21	2.50
	32	205	194.354	20	21	2.68
	33	211	200.408	20	21	2.85
	34	217	206.463	20	21	3.02
	35	223	212.518	20	21	3.25
	36	229	218.574	20	21	3.40
	37	235	224.631	20	21	3.60
	38	241	230.687	20	21	3.80
	39	247	236.744	20	21	4.00
	40	253	242.802	20	21	4.20