



SUS80B

SUS Stainless Steel Sprocket B-type

Order Product Code

SUS80B 20

TYPE No. of Teeth
Sprocket No.



- Chain **No.80**
- Chain Pitch **(P) 25.4 mm**
- Roller Link Inner Width ... **(W) 15.88 mm**
- Roller Outside Diameter ... **(Dr) 15.88 mm**
- Tooth Width **(T) 14.6 mm**

Use together with the KANA machine key.
Refer to P.334 to P.335

m Stainless Steel **GB** 304

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d			BD	BL	Shape	Weight kg
				Prepared Hole	Minimum	Maximum				
SUS80B	10	93	82.196	15	16	32	52	40	Ground Specification	1.02
	11	102	90.156	15	16	38	60	40		1.25
	12	110	98.138	15	16	45	67	40		1.60
	13	118	106.136	16	17	51	77	40		1.90
	14	127	114.147	16	17	51	77	40		2.15
	15	135	122.167	20	21	63	93	40		2.30
	16	143	130.196	20	21	63	93	40		2.50
	17	151	138.232	20	21	63	93	40		2.95
	18	159	146.273	20	21	63	93	40		3.15
	19	167	154.319	20	21	63	93	40		3.40
	20	176	162.368	20	21	63	93	40		3.60
	21	184	170.421	20	21	63	93	40		3.85
	22	192	178.478	26	27	63	93	45		5.00
	23	200	186.536	26	27	63	93	45		5.23
	24	208	194.597	26	27	63	93	45		5.50
	25	216	202.660	26	27	63	93	45		5.80
	26	224	210.724	26	27	63	93	45		6.10
	27	233	218.790	26	27	63	93	45		6.40
	28	241	226.858	26	27	63	93	45		6.75
	30	257	242.996	26	27	63	93	45		7.40
32	273	259.138	26	27	63	93	45	8.15		
34	289	275.284	26	27	63	93	45	8.90		
35	297	283.358	26	27	63	93	45	9.30		
40	338	323.736	26	27	75	107	50	12.40		



Caution

*Because teeth number 22 to 40 are being shifted from welding specification to grinding specification, the inventory is currently mixed.