

KANA NK50C



●ご注文方法 商品コード

NK50C 20

TYPE 歯数


- チェーンNo.50
- チェーンピッチ(P)15.875mm
- ローリンク内幅(W) 9.53 mm
- ローラ外径(Dr)10.16 mm
- 歯幅(T) 8.9(最大) mm




削出仕様



溶接仕様



削出仕様



溶接仕様

| 商品コード | 定価 (円) | SEMI-F 定価(円) | SEMI-FA/FAP 定価(円) | 外径 Do | ピッチ径 Dp | 軸穴径 d | | | ボス径 BD | ボス長さ BL | 形状 | 歯部 | 質量 (kg) |
|---------|--------|-----------------|----------------------|----------|------------|-------|----|----|-----------|------------|-------|----------------------------|------------|
| | | | | | | 下穴 | 最小 | 最大 | | | | | |
| NK50C10 | 1,700 | 6,600 | 5,600 | 58 | 51.373 | 10 | 11 | 19 | 33 | 40 | 削出仕様 | h m 歯先高周波焼入 機械構造用炭素鋼 | 0.33 |
| NK50C11 | 1,800 | 6,800 | 5,800 | 64 | 56.348 | 12 | 13 | 22 | 38 | 40 | | | 0.43 |
| NK50C12 | 1,900 | 6,900 | 5,900 | 69 | 61.336 | 12 | 13 | 24 | 43 | 40 | | | 0.50 |
| NK50C13 | 2,100 | 7,100 | 6,000 | 74 | 66.335 | 12 | 13 | 24 | 48 | 40 | | | 0.65 |
| NK50C14 | 2,400 | 7,500 | 6,400 | 79 | 71.342 | 12 | 13 | 28 | 53 | 40 | | | 0.80 |
| NK50C15 | 2,600 | 7,700 | 6,500 | 84 | 76.355 | 12 | 13 | 32 | 58 | 40 | | | 0.90 |
| NK50C16 | 2,800 | 7,900 | 6,700 | 89 | 81.373 | 14 | 15 | 35 | 63 | 40 | | | 1.05 |
| NK50C17 | 3,200 | 8,400 | 7,100 | 94 | 86.395 | 14 | 15 | 39 | 68 | 40 | | | 1.25 |
| NK50C18 | 3,400 | 8,700 | 7,400 | 100 | 91.420 | 14 | 15 | 45 | 73 | 40 | | | 1.40 |
| NK50C19 | 3,600 | 9,000 | 7,700 | 105 | 96.449 | 14 | 15 | 47 | 78 | 40 | | | 1.60 |
| NK50C20 | 3,900 | 9,200 | 7,800 | 110 | 101.480 | 14 | 15 | 52 | 80 | 40 | | | 1.70 |
| NK50C21 | 4,100 | 9,500 | 8,100 | 115 | 106.513 | 14 | 15 | 55 | 85 | 40 | | | 1.90 |
| NK50C22 | 4,600 | 10,100 | 8,600 | 120 | 111.548 | 16 | 17 | 60 | 90 | 40 | | | 2.15 |
| NK50C23 | 5,300 | 10,900 | 9,300 | 125 | 116.585 | 16 | 17 | 63 | 95 | 40 | | | 2.40 |
| NK50C24 | 5,900 | 11,700 | 9,900 | 130 | 121.623 | 16 | 17 | 67 | 100 | 40 | | | 2.55 |
| NK50C25 | 6,000 | 11,700 | 9,900 | 135 | 126.662 | 16 | 17 | 70 | 100 | 40 | | | 2.65 |
| NK50C26 | 6,500 | 12,300 | 10,500 | 140 | 131.703 | 16 | 17 | 70 | 100 | 40 | | | 2.70 |
| NK50C27 | 6,500 | 12,400 | 10,500 | 145 | 136.744 | 16 | 17 | 70 | 100 | 40 | | | 2.85 |
| NK50C28 | 7,100 | 13,000 | 11,100 | 150 | 141.786 | 16 | 17 | 70 | 100 | 40 | | | 2.90 |
| NK50C30 | 7,800 | 13,800 | 11,700 | 161 | 151.873 | 16 | 17 | 70 | 100 | 40 | 3.50 | | |
| NK50C32 | 8,500 | 14,700 | 12,500 | 171 | 161.961 | 16 | 17 | 80 | 120 | 40 | 4.10 | | |
| NK50C34 | 9,300 | 15,600 | 13,300 | 181 | 172.052 | 16 | 17 | 80 | 120 | 40 | 4.20 | | |
| NK50C35 | 9,300 | 15,600 | 13,300 | 186 | 177.099 | 16 | 17 | 80 | 120 | 40 | 4.40 | | |
| NK50C36 | 15,300 | 25,000 | 21,300 | 191 | 182.145 | 19 | 20 | 55 | 83 | 50 | 3.30 | | |
| NK50C38 | 16,700 | 26,700 | 22,700 | 201 | 192.239 | 19 | 20 | 55 | 83 | 50 | 3.50 | | |
| NK50C40 | 18,100 | 28,400 | 24,100 | 211 | 202.335 | 19 | 20 | 55 | 83 | 50 | 3.80 | | |
| NK50C42 | 20,000 | 30,600 | 26,000 | 221 | 212.431 | 19 | 20 | 55 | 83 | 50 | 4.00 | | |
| NK50C45 | 21,800 | 32,700 | 27,800 | 237 | 227.577 | 19 | 20 | 55 | 83 | 50 | 4.30 | | |
| NK50C48 | 25,400 | 37,000 | 31,500 | 252 | 242.725 | 19 | 20 | 55 | 83 | 50 | 4.70 | | |
| NK50C50 | 27,500 | 42,100 | 35,800 | 262 | 252.825 | 19 | 20 | 55 | 83 | 50 | 5.00 | | |
| NK50C54 | 31,800 | 47,200 | 40,100 | 282 | 273.025 | 19 | 20 | 55 | 83 | 50 | 5.60 | | |
| NK50C60 | 44,900 | 65,000 | 55,300 | 312 | 303.329 | 19 | 20 | 63 | 93 | 60 | 7.40 | | |
| NK50C65 | 25,000 | 41,500 | 35,300 | 338 | 328.584 | 20 | 21 | 63 | 93 | 60 | 8.30 | | |
| NK50C70 | 26,000 | 51,600 | 43,900 | 363 | 353.841 | 20 | 21 | 63 | 93 | 60 | 9.20 | | |
| NK50C75 | 28,400 | 54,400 | 46,200 | 388 | 379.099 | 20 | 21 | 63 | 93 | 60 | 10.20 | | |

※SEMI-Fシリーズ<完成品>のご注文方法はP.40～P.53を参照ください。